

MATERIAL TYPE	:	COMPRESSED ASBESTOS FIBER (CAF)
THICKNESS	:	0.25mm, 0.5mm, 0.8mm, 1mm, 1.5mm, 2mm, 3mm, 4mm, 5mm , 6mm (OTHER THICKNESS ON REQUEST)
SURFACE FINISH	:	Red, Grey , Graphited (OTHER COLORS ON REQUEST)
DIMENSIONS OF SHEETS	:	1500MM X3100MM, 1500MM X1500MM, 1500MM X 1000MM, 1500MM X 2000MM, 1270MM X 1270MM, 1270MM X 3810MM, 3000MM X 3000MM
OPERATING CONDITION	:	Maximum pressure : 35 Bar Maximum Temperature: 350
SPECIFICATION COMPLIANCE	:	IS: 2712 / 1998 GRADE W / 3

The following Information Applies to material Thickness 1.5mm.

S.NO.	Typical Properties	Test Method	Unit	Specified Value
1	DENSITY	IS:2712/1998	G/cm3	2.20
2	TENSILE STRENGTH	IS:2712/1998	Mpa	>6.7
3	COMPRESSIBILITY IS:2712/1998	IS:2712/1998	%	6 -14
4	RECOVERY	IS:2712/1998	%	>40
5	FLEXIBILITY	IS:2712/1998	-	No Visual
6	IGNITION LOSS	IS:2712/1998	%	<28